

- 520 TVL of horizontal resolution (EQ300E)
- Support video drive and DC drive auto IRIS lens
- Designed with advance digital signal processing circuitry for high image quality
- Day/Night Auto/Off switchable
- ES, Blc, AGC and FI On/Off switchable
- Compatible with both C-mount and CS-mount lens (adapter ring included)
- System available for NTSC or PAL

Pickup Device	1/3" SONY Super HAD CCD	
Video Format	NTSC /PAL	
Scanning System	NTSC: 525 TVL, 60 fields/sec; PAL: 625 TVL, 50 fields/sec.	
Picture Elements	510 x 492 (NTSC); 500 x 582 (PAL)	768 x 494(NTSC); 752 x 582 (PAL)
Horizontal Resolution	380TVL	520TVL
Sensitivity	0.3 Lux/F=1.2	0.4 Lux/F=1.2
S/N Ratio	Over 48dB (AGC off)	
Electronic Shutter	1/50(1/60)~1/100,000	
Auto Iris	Video Drive/Direct Drive switch	
Back Light Comp.	ON/OFF Switch	
Auto Gain Control	ON/OFF Switch	
Flickerless	On/Off switch	
Day & Night Mode	Auto/Off switch	
Auto White Balance	Yes	
Gamma Correction	0.45	
Video Output	BNC 1.0Vp-p,75 ohm	
Sync. Mode	Internal sync	
Lens Mount	C/CS mount	
Audio	Optional	
Power Source	3 types: 12VDC only; 12VDC/24VAC; 100VAC~240VAC	
Power Consumption	12VDC: 1,6W max..	
	24VAC: 2,2W max..	
	100VAC~240VAC: 1.6W max.	
Dimensions	58mm (W) x 55mm (H) x 125mm(D); 2.3"(W) x 2.2"(H) x 4.9"(D)	
Weight	0.25kg ; 0.55lbs	
Operating Temperature	0°C ~ 50°C ; 32°F~122°F (20%~80% Humidity)	
Lens	Len sold separately	
Certifications	FCC/CE	