

- Low light sensitivity 0.5 Lux/F=1.2(AGC ON) is achieved by using the advanced 1/3" SONY Super HAD CCD
- 560 TVL of horizontal resolution
- Revolutionary integrated 10-bit Digital Signal Processor (DSP) delivers excellent picture quality an sharp color images
- Intelligent backlight compensation
- Utilizes Pure Vision Technology

Pickup Device	1/3" SONY Super HAD CCD
<b>Video Format</b>	NTSC or PAL
<b>Scanning System</b>	NTSC: 525 TVL, 60 fields/sec; PAL: 625 TVL, 50 fields/sec.
<b>Picture Elements</b>	768 x 494 (NTSC); 752 x 582 (PAL)
<b>Horizontal Resolution</b>	560 TVL
<b>Sensitivity</b>	0.5 Lux/F=1.2
<b>S/N Ratio</b>	Over 48dB(AGC off)
<b>Electronic Shutter</b>	1/50 (1/60) ~ 1/100,000
<b>Lens Type</b>	Vari-focal lens, Auto Iris f = 3,8~9.5mm, F=1.2
<b>Back Light Comp.</b>	On/Off switch
<b>Auto Gain Control</b>	On/Off switch
<b>Flickerless</b>	On/Off switch
<b>Auto White Balance</b>	Yes
<b>Gamma Correction</b>	0.45
<b>Video Output</b>	BNC 1.0Vp-p,75 ohm
<b>Sync. Mode</b>	Line Lock/Internal Sync
<b>Power Source</b>	12VDC/24VAC
<b>Power Consumption</b>	24VAC: 7.5VA max. 12VDC: 4.5W max.
<b>Dimensions</b>	66mm(W) x 59mm(H) x 146mm(D) 2.56"(W) x 2.3"(H) x 5.7"(D)
<b>Weight</b>	0.4kg; 0.9lbs
<b>Mounting Bracket</b>	Aluminum, Dimension 145mm(H) x 56.5mm(O.D.) / 5.7"(H) x 2.2"(O.D.); Max Load 3kgs
<b>Operating Temperature</b>	0°C~50°C ; 32°F~122°F (20%-80% Humidity)
<b>Service Kit</b>	Mounting bracket x 1 pcs
<b>Certifications</b>	FCC/CE

